

SAFETY DATA SHEET



Date Prepared : 11/25/2013
 MSDS No : 15359-GHS - RESIN
 Date-Revised : 06/23/2016
 Revision No : 7

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: 6GM METAL EPOXY - RESIN

MANUFACTURER

Pacer Technology
 3281 E. Guasti Rd., Suite 260
 Ontario, CA 91761

Emergency Contact: CHEMTREC

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887

Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Skin Irritation, Category 2

Eye Irritation, Category 2A

Skin Sensitization, Category 1

Environmental:

Aquatic Hazard (Long-Term), Category 2

GHS LABEL ELEMENTS

Exclamation
 mark



Health
 hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENT(S)**Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash skin and hands thoroughly after handling.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P362: Take off contaminated clothing.

P363: Wash contaminated clothing before reuse.

SAFETY DATA SHEET



Date Prepared : 11/25/2013
 MSDS No : 15359-GHS - RESIN
 Date-Revised : 06/23/2016
 Revision No : 7

P391: Collect spillage.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Epoxy resin, BPA	80 - 100	25068-38-6
Bisphenol F epoxy resin	1 - 10	9003-36-5

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, do not induce vomiting. Keep individual calm. Get medical attention and show container label.

INHALATION: Remove to fresh air. Get medical attention if breathing is difficult.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Irritating to skin. May cause allergic skin reaction with prolonged contact.

SKIN ABSORPTION: None known.

INGESTION: May be irritating. Seek medical advice.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Decomposition and products may be toxic. Thermal breakdown of the product during fired or very high heat conditions may product the following: carbon monoxide, carbon dioxide, and isobutene.

EXPLOSION HAZARDS: None known.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may

SAFETY DATA SHEET



Date Prepared : 11/25/2013
MSDS No : 15359-GHS - RESIN
Date-Revised : 06/23/2016
Revision No : 7

result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: None known.

SENSITIVE TO STATIC DISCHARGE: None known.

SENSITIVITY TO IMPACT: None Known.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion products may include: carbon monoxide, carbon dioxide, hydrogen gas and oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid and place in sealed container for disposal

LARGE SPILL: Contain spill with dike to prevent entry into sewers. Absorb liquid and place in sealed container for disposal.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LAND SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

AIR SPILL: None known.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes, and clothing. Keep Container closed when not in use.

STORAGE: Store in a cool place in original container and protect from sunlight. Protect from freezing.

STORAGE TEMPERATURE: Ambient room temperature (70F/21C).

LOADING TEMPERATURE: Not Established

LOADING/UNLOADING VISCOSITY: Not Established

STORAGE PRESSURE: Not Established

ELECTROSTATIC ACCUMULATION HAZARD: None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Not Established

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Wear rubber gloves to avoid prolonged skin contact.

RESPIRATORY: In case of insufficient ventilation, wear suitable respiratory equipment.

PROTECTIVE CLOTHING: Wear rubber gloves and apron.

WORK HYGIENIC PRACTICES: Avoid contact with skin and eyes. Wash thoroughly after handling.

SAFETY DATA SHEET



Date Prepared : 11/25/2013
MSDS No : 15359-GHS - RESIN
Date-Revised : 06/23/2016
Revision No : 7

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid.
ODOR: Moderate odor.
ODOR THRESHOLD: No data available
APPEARANCE: Light yellow viscous liquid.
pH: No data available
PERCENT VOLATILE: No data available
FLASHPOINT AND METHOD: > 93°C (200°F) CC - Closed Cup
AUTOIGNITION TEMPERATURE: No data available
VAPOR PRESSURE: No data available
VAPOR DENSITY: No data available
BOILING POINT: No data available
FREEZING POINT: No data available
MELTING POINT: No data available
POUR POINT: No data available
THERMAL DECOMPOSITION: No data available
SOLUBILITY IN WATER: Insoluble
EVAPORATION RATE: No data available
DENSITY: No data available
SPECIFIC GRAVITY: 1.16
VISCOSITY #1: 20000 to 40000 Centipoise
Notes: No data available
MOLECULAR WEIGHT: No data available
(VOC): No data available

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No
STABILITY: Stable
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition or burning may release oxides of carbon and nitrogen.
INCOMPATIBLE MATERIALS: Strong oxidizing agents, acids and bases.

11. TOXICOLOGICAL INFORMATION

ACUTE

SAFETY DATA SHEET



Date Prepared : 11/25/2013
 MSDS No : 15359-GHS - RESIN
 Date-Revised : 06/23/2016
 Revision No : 7

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
Epoxy resin, BPA	> 2000 mg/kg (rat)	> 2000 mg/kg (rat)
Bisphenol F epoxy resin	> 5000 mg/kg (rat)	> 2000 mg/kg (rat)

EYE EFFECTS: Mildly to moderately irritating.

SKIN EFFECTS: Irritating to skin. May cause allergic reaction with prolonged contact.

CARCINOGENICITY

IARC: Not listed.

NTP: Not listed.

OSHA: Not listed.

REPEATED DOSE EFFECTS: None known.

IRRITATION: Prolonged or repeated skin contact may cause irritation and/or dermatitis.

CORROSIVITY: None known.

SENSITIZATION: May cause sensitization.

NEUROTOXICITY: None known.

GENETIC EFFECTS: None known.

REPRODUCTIVE EFFECTS: None known.

TARGET ORGANS: None known.

MUTAGENICITY: None known.

SYNERGISTIC MATERIALS: None known.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Do not flush to sewer.

ECOTOXICOLOGICAL INFORMATION: No data available for this product.

BIOACCUMULATION/ACCUMULATION: No data available on this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

PRODUCT DISPOSAL: Avoid runoff into storm sewers and ditches which lead to waterways.

SAFETY DATA SHEET



Date Prepared : 11/25/2013
 MSDS No : 15359-GHS - RESIN
 Date-Revised : 06/23/2016
 Revision No : 7

EMPTY CONTAINER: Dispose of following all Local Authority requirements for disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN3082, Environmentally hazardous substance, liquid, N.O.S. (Bisphenol A Epoxy Resin, Bisphenol F Epoxy Resin), 9, III, Marine Pollutant

AIR (ICAO/IATA)

SHIPPING NAME: UN3082, Environmentally hazardous substance, liquid, N.O.S. (Bisphenol A Epoxy Resin, Bisphenol F Epoxy Resin), 9, III, Marine Pollutant

VESSEL (IMO/IMDG)

SHIPPING NAME: UN3082, Environmentally hazardous substance, liquid, N.O.S. (Bisphenol A Epoxy Resin, Bisphenol F Epoxy Resin), 9, III, Marine Pollutant

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

TITLE III NOTES: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Epoxy resin, BPA	25068-38-6

CALIFORNIA PROPOSITION 65

Chemical Name	Wt.%	Listed
Epoxy resin, BPA	80 - 100	● Female Reproductive

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department


PREPARED BY: Pacer Technology Regulatory Department

Date-Revised: 06/23/2016

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER:

SAFETY DATA SHEET



Date Prepared : 11/25/2013

MSDS No : 15359-GHS - RESIN

Date-Revised : 06/23/2016

Revision No : 7

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: 6GM METAL EPOXY - HARDENER

MANUFACTURER

Pacer Technology
 3281 E. Guasti Rd., Suite 260
 Ontario, CA 91761

Emergency Contact: CHEMTREC

Emergency Phone: 800-424-9300

Alternate Emergency Phone: 703-527-3887

Product Stewardship: 909-987-0550

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Skin corrosion/Irritation, Category 1C

Serious eye damage/irritation, Category 1

Specific Target Organ Toxicity (Repeated Exposure): Oral [brain], Category 2

GHS LABEL ELEMENTS

Corrosion

Health
hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated exposure if swallowed. (brain)

PRECAUTIONARY STATEMENT(S)**General:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

Prevention:

P202: Do not handle until all safety precautions have been read and understood.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P264: Wash skin and hands thoroughly after handling.

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

P270: Do not eat, drink, or smoke when using this product.
 P272: Contaminated work clothing should not be allowed out of the workplace.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P281: Use personal protective equipment as required.
 P362: Take off contaminated clothing.

Response:

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+352: IF ON SKIN: Wash with plenty of soap and water.
 P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313: IF exposed or concerned: Get medical advice/ attention.
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
 P337: If eye irritation persists: seek medical attention.
 P362: Take off contaminated clothing.
 P391: Collect spillage.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of in a manner consistent with federal, state, and local regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Mercaptan terminated polymer	60 - 100	
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	1 - 10	90-72-2
Bis(dimethylamino)methyl phenol	1 - 5	71074-89-0

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Get medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms reoccur. Wash clothing before reuse.

INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes eye irritation.

SKIN: Contact causes skin irritation.

INGESTION: Ingestion of this material can cause mouth, throat, esophageal, and gastrointestinal tract irritation.

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE EFFECTS: Slightly irritating to eyes and respiratory tracts.

CHRONIC EFFECTS: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Decomposition and combustion products may be toxic.

EXPLOSION HAZARDS: None known.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

FIRE EXPLOSION: None known.

SENSITIVE TO STATIC DISCHARGE: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Polymerize with water. Solid material may be scraped from surface.

LARGE SPILL: Absorb the liquid and scrub the area with detergent and water. Avoid runoff into storm sewers and ditches which lead to waterways.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

LAND SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

AIR SPILL: None known

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Ambient room temperature (70F/21C).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use only in a well ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

SKIN: Avoid contact with skin.

RESPIRATORY: Use only in a well ventilated area.

PROTECTIVE CLOTHING: Launder contaminated clothing before reuse.

WORK HYGIENIC PRACTICES: Avoid contact with skin and eyes. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid. [Paste].

ODOR: Epoxy odor.

ODOR THRESHOLD: No data available

APPEARANCE: Light gray thick liquid.

pH: No data available

PERCENT VOLATILE: No data available

FLASHPOINT AND METHOD: > 93°C (199.4°F) CC - Closed Cup

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: No data available

VAPOR DENSITY: No data available

BOILING POINT: No data available

FREEZING POINT: No data available

MELTING POINT: No data available

POUR POINT: No data available

THERMAL DECOMPOSITION: No data available

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE: No data available

DENSITY: 1.15 to 1.25 g/cm³

SPECIFIC GRAVITY: 1.15 to 1.25

VISCOSITY #1: 60000 to 90000 Centipoise at 25 °C (77°F)

MOLECULAR WEIGHT: No data available

(VOC): No data available

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable

CONDITIONS TO AVOID: Avoid storage near large masses of epoxy resins.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide, hydrogen sulfide and oxides of sulfur.

INCOMPATIBLE MATERIALS: Avoid strong oxidizing agents and amines especially when hot.

11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	2169 mg/kg (rat)	> 971 mg/kg (rat)

EYE EFFECTS: Mildly to moderately irritating.

SKIN EFFECTS: Irritating to skin. May cause allergic skin reaction with prolonged contact.

CARCINOGENICITY

IARC: Not listed.

NTP: Not listed.

OSHA: Not listed.

SENSITIZATION: Irritating to skin. May cause allergic skin reaction with prolonged contact.

TERATOGENIC EFFECTS: No data available.

MUTAGENICITY: No data available.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Do not flush to sewer.

BIOACCUMULATION/ACCUMULATION: No data available.

GENERAL COMMENTS: Prevent product from entering drains or sewers in case of spill.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal of following all Local Authority requirements for disposal.

FOR LARGE SPILLS: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on adsorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL), 8, III

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL), 8, III

AIR (ICAO/IATA)

SHIPPING NAME: UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL), 8, III

VESSEL (IMO/IMDG)

SAFETY DATA SHEET



Date Prepared : 03/28/2014
 MSDS No : 15359-GHS - HARDENER
 Date-Revised : 06/28/2016
 Revision No : 5

SHIPPING NAME: UN2735, POLYAMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL), 8, III

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	90-72-2

TSCA STATUS: All ingredients in this mixture are in compliance with TSCA.

CALIFORNIA PROPOSITION 65: No California Proposition 65 ingredients are known to be in this product.

16. OTHER INFORMATION

APPROVED BY: Pacer Technology Regulatory Department


PREPARED BY: Pacer Technology Regulatory Department **Date-Revised:** 06/28/2016

REVISION SUMMARY: This MSDS replaces the 05/26/2015 MSDS. Revised: **Section 1:** APPROVED BY, Date Issued, PREPARED BY, TITLE. **Section 2:** EMERGENCY OVERVIEW (PHYSICAL APPEARANCE), IRRITANCY, MEDICAL CONDITIONS AGGRAVATED, POTENTIAL HEALTH EFFECTS (SKIN, INHALATION, INGESTION), ROUTES OF ENTRY, SENSITIZATION. **Section 3:** Wt.%. **Section 6:** GENERAL PROCEDURES, SPECIAL PROTECTIVE EQUIPMENT. **Section 7:** SHELF LIFE. **Section 9:** AUTOIGNITION TEMPERATURE, BOILING POINT, DENSITY, EVAPORATION RATE, FLASHPOINT AND METHOD, FREEZING POINT, MELTING POINT, MOLECULAR WEIGHT, ODOR, ODOR THRESHOLD, PERCENT VOLATILE, pH, PHYSICAL STATE, POUR POINT, SOLUBILITY IN WATER, SPECIFIC GRAVITY, VAPOR PRESSURE, VISCOSITY, (VOC), THERMAL DECOMPOSITION, . **Section 10:** STABLE. **Section 11:** IARC, MUTAGENICITY, NTP, OSHA, TERATOGENIC EFFECTS. **Section 12:** GENERAL COMMENTS, BIOACCUMULATION/ACCUMULATION. **Section 13:** EMPTY CONTAINER, PRODUCT DISPOSAL. **Section 14:** AIR (ICAO/IATA) - SHIPPING NAME DOT (DEPARTMENT OF TRANSPORTATION) - PROPER SHIPPING NAME ROAD AND RAIL (ADR/RID) - PROPER SHIPPING NAME SHIPPING NAME, VESSEL (IMO/IMDG) - SHIPPING NAME. **Section 15:** ACUTE, CHRONIC, FIRE, PRESSURE GENERATING, REACTIVITY, WHMIS CLASS. **Section 16:** HMIS RATING (PHYSICAL HAZARD), NFPA CODES (REACTIVITY).

HMIS RATING

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, Pacer Technology does not assume any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is

SAFETY DATA SHEET



Date Prepared : 03/28/2014
MSDS No : 15359-GHS - HARDENER
Date-Revised : 06/28/2016
Revision No : 5

the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.